

SFX/5304FE-LSZH-BLU

5304FE 6 x 7 x 0.4 18AWG Blue LSZH



Cable Construction	
	6 Cores
Conductor	Bare Copper
Conductor Diameter (mm)	0.40 ±0.008 x 7
Stranded Diameter (mm)	1.22
Insulation	PP
Insulation Thickness (mm)	0.19
Insulation Diameter (mm)	1.60 ±0.10
Insulation Colours	Black, White, Red, Green, Brown, Blue
Al-PET Shield	≥115%
Drain Wire	
Conductor	Tinned Copper
Conductor Diameter (mm)	0.20 ±0.008 x 7
Nylon Rip-Cord	White 150D
Jacket	LSZH
Jacket Thickness (mm)	0.50 ±0.10
Overall Diameter (mm)	5.69 ±0.20
Jacket Colour	Blue RAL 5015
Sheath Printing	6 x 18AWG Overall Screened LSZH RoHS2 (PO) (m)
Reaction to Fire	Fca
Electrical Characteristics	
Max Conductor DC resistance @ 20°C	<21.10Ω/km
Rated Temperature	70°C
Rated Voltage	300V
Insulation Resistance @20°C	>200MQ/km



www.securiflex.co.uk

Every care is taken to ensure all information in this publication is correct. No Legal responsibility can be accepted for any inaccuracy.
The company reserves the right to alter or modify the information of this specification without notice. E&OE. Registered in England & Wales, Company No.03758330. VAT Number: 736 5084 24.