



**6701B**

## MINI MONITOR WITH HANDSET. BLACK. S2 SYSTEM



Wall-mounted monitor with 4.3" 16/9 colour screen and handset. Allows brightness and colour control, plus adjustment of the volume of the ringtone, which can be customised with a choice of different melodies. Equipped as standard with 8 soft touch buttons for door-opening, self-ignition, switchboard call and privacy service functions and with door status indicator LEDs. Manages floor door calls as standard. Complete with 2 x 8-position DIP-switches for user code programming and button programming. Includes wall-mounting or residential series box backplate and riser distribution terminal Art. 1214/2C. The monitor can only be used in 2-wire Simplebus2 systems. Dimensions: 175x160x22mm.

### AWARDS

DESIGN  
MILANO





**6701B**

**MINI MONITOR WITH HANDSET. BLACK. S2 SYSTEM**

**GENERAL DATA**

|                     |               |
|---------------------|---------------|
| Product height (mm) | 160           |
| Product width (mm)  | 175           |
| Product depth (mm)  | 22            |
| Product weight (g)  | 600           |
| Product color       | Black RAL9005 |
| Material            | ABS           |
| Wall-mounted        | Yes           |

**COMPATIBLE SYSTEMS**

|   |     |
|---|-----|
| Audio/video Simplebus 2 with power supply art. 4888C      | Yes |
| Audio/video Simplebus 2 with power supply art. 1210/1210A | Yes |
| Simplebus 2 audio/video kit with power supply art. 1209   | Yes |

**DISPLAY FEATURES**

|                     |         |
|---------------------|---------|
| Size (inches) (")   | 4.3     |
| Aspect Ratio        | 16:9    |
| Resolution (pixels) | 480x272 |

**AUDIO FEATURES**

|             |                                    |
|-------------|------------------------------------|
| Microphone  | 6mm (Ø), Omnidirectional           |
| Loudspeaker | 40 (Ø) x 5.1 (H)mm, 100 ohm, 0.25W |

**ELECTRICAL CHARACTERISTICS**

|                        |  |
|------------------------|--|
| Type of power supply   | Power supply from video door entry bus |
| Supply voltage         | 22÷34 VDC (Bus)                        |
| Maximum absorption (W) | 5.4                                    |

**HARDWARE FEATURES**



## 6701B

### MINI MONITOR WITH HANDSET. BLACK. S2 SYSTEM

|  |   |
|--|---|
| Type of buttons                                      | Capacitive                                |
| Service buttons                                      | Lock-release, Silent (Privacy), Door open |
| No. of programmable buttons for additional functions | 6   |
| Clamps   | L L CFP1 CFP2                             |
| Removable terminals                                  | Yes                                       |

#### SETTINGS

|                   |     |
|-------------------|-----|
| Ringtone volume   | Yes |
| Screen brightness | Yes |
| Screen colour     | Yes |

#### ENVIRONMENTAL AND COMPLIANCE FEATURES

|                                     |  |
|-------------------------------------|--|
| IP protection degree                | IP30   |
| Operating temperature (°C)          | 5 ÷ 40   |
| Operating humidity (RH max - %) (%) | 25 ÷ 75  |
| Environmental class                 | I  |
| Compliance and Certifications       | RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011) |

#### MAIN FUNCTIONS

|                               |     |
|-------------------------------|-----|
| Door opener                   | Yes |
| Self Activation               | Yes |
| Intercom calls                | Yes |
| Actuator control              | Yes |
| CPS call                      | Yes |
| Outside door call input       | Yes |
| Silent mode (Privacy)         | Yes |
| Door opening on call (Doctor) | Yes |
| Door open signaling           | Si  |
| Call forwarding               | Yes |
| Multiple address              | Yes |



**6701B**

## MINI MONITOR WITH HANDSET. BLACK. S2 SYSTEM

### MAIN FUNCTIONS

|                       |     |
|-----------------------|-----|
| Customisable ringtone | Yes |
| Sending alarm calls   | Yes |