

PRODUCT

FV-PRO 9584SB-2.8 - NEW 4K 8MP Enhanced IP Mini Eyeball with IR LED & Built-in Audio



8MP (3840 × 2160) H.265 coding

Max.resolution: 3840 × 2160

Now with Built-in Audio!

ICR auto switch, true day / night, ROI coding

3D DNR, digital WDR, HLC, BLC, Smart IR, defog

20~30m IR night view distance

Support smart phone, iPad, remote monitoring

DC12V/PoE power supply

P2P function optional

IP 67 ingress protection

Support three streams

Smart analytics (optional): object removal detection, abnormal video signal detection, line crossing detection and region intrusion detection

DETAILS

ADDITIONAL INFORMATION

AES	Yes
AGC	Auto
Aperture Correction	H aperture V aperture
BLC	Yes
BLC/SSDR (WDR)	Digital WDR
Communication System	IP
Compression Method	H.265/H.264 / MJPEG
Connection Cable	DC + POE
DNR	2D/3D DNR
Dimensions	Ø 94.6mm×82.8mm
Dual Streaming	Support three streams
Effective Pixel	3840 x 2160
Gamma Correction	0.45
Gross Weight	Approx. 0.45KG
IR Illumination	Up to 30m
Image Sensor (CCD)	1/2.5" 8 Megapixel

Lens	3.6 mm @F1.6, horizontal field of view: 87.7°
Minimum Illumination - Colour	0.024 lux @F1.2, AGC ON
Minimum Illumination - Mono	0 lux with IR
Model	9584S2
POE	Yes
Power Consumption	<6W
Power Source	12V DC Regulated or POE
S/N Ratio	55db +
Scanning System	PAL
Shutter	Auto
Sync System	2:1 Internal
Video Output Signal	1.0vp-p, 75 ohm composite
Within Range of IR LEDs	Up to 30m