



Page 1 of 7 Issued: 09/06/2025 Revision No.3 Regulation (EC) No.453/2010

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1 Product Identifier

Material name : DETECTASMOKE DSF1 DSF2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Smoke Detector Tester

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Gas Safe Europe Ltd.,

Chowley One Tattenhall Chester Cheshire CH3 9GA

Tel. : +44 (0) 1352 860600

Fax.

Email (for SDSs): enquiries@gassafeeurope.com

1.4 Emergency tel. no.: +44 (0) 1352 860600 (Office hours)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

According to 1272/2008/EC: Classification, Labelling and Packaging of Substances and Mixtures (CLP) Regulation:

Extremely Flammable Aerosol Category1

2.2 Label elements

Labelling according to EC Directives: 1272/2008/EC:

Signal word: Danger



Pictogram(s):

H-Statements: H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

P-Statements: P261 Avoid breathing vapour/spray.

P271 Use only outdoors or in a well-ventilated area.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C.

Page 2 of 7 Issued:9/06/2025; Revision No.3 Regulation (EC) No. 453/2010

2.3 Other hazards

In use, may form flammable / explosive vapour-air mixture.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Mixtures:

Hazardous components

Chemical Name	CAS No./ EC No./ Reg. No	Classification (1272/2008/EC)	Content
LIQUEFIED PETROLEUM GAS (contains <0.1% 1,3-butadiene)	68476-85-7 270-704-2 -	Flam.Gas 1; H220 Gas under pressure; H280	>90%

See Section 16 for the full text of the H-statements noted above.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice: Remove casualty from exposure ensuring one's own safety whilst doing so. Take off any contaminated clothing and shoes/boots immediately. Never give anything by mouth to an unconscious person.

Skin contact: Wash with soap and water. Seek medical advice if irritation develops.

Eye contact: Rinse with water for 10 minutes and seek medical advice if irritation persists.

Ingestion: Rinse mouth with water and give water to drink. Do not induce vomiting. Seek medical advice.

Inhalation: Remove to fresh air. Seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed: No specific concerns.

4.3 Indication of any immediate medical attention and special treatment needed: No specific concerns.

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Carbon dioxide; dry chemical powder; alcohol or polymer foam.

Unsuitable extinguishing media: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting: Irritating/toxic fumes may be released at elevated temperatures.

5.3 Advice for fire-fighters:

Special protective equipment: Wear self-contained breathing apparatus. Use personal protective equipment.

Further information: Standard procedure for chemical fires. Use water spray to cool containers.

Do not allow fire run-off to enter drains.

Page 3 of 7 Issued:09/06/2025; Revision No3 Regulation (EC) No. 453/2010

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Use personal protective equipment to deal with spillage.

6.2 Environmental precautions

Contain the spillage using sufficient appropriate absorbent material. Do not discharge into drains or rivers, but if contamination to waterways has occurred, inform local authorities.

6.3 Methods and materials for containment and cleaning up

Wipe up liquid spillage with absorbent material such as sand, earth, or vermiculite, and place in a labelled container for disposal in accordance with local/national regulations.

6.4 References to other sections

See sections 8 and 13 for personal protection and disposal information.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Do not breathe spray mist. Handle with care.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, well ventilated area, below 50°C. Protect from frost, heat and sunlight. Keep away from food, drink and animal feed.

7.3 Specific end use(s): No information available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Chemical name	8hr TWA	15min STEL	Reference
Liquefied petroleum gas	1750 mg/m ³ /1000ppm	$2810 \text{ mg/m}^3/1250 \text{ ppm}$	EH40/2005

8.2 Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Personal protective equipment

Respiratory protection: Unlikely to be necessary in normal circumstances; if vapour levels are high, wear a respirator conforming to EN 140 with type A filter or better.

Hand protection: Gloves not normally required.

Eye protection: Chemical splash goggles if eye contact is reasonably probable. The selected goggles or glasses must satisfy the European standard EN 166.

Skin and body protection: General workwear.

Page 4 of 7 Issued: 09/06/2025; Revision No3 Regulation (EC) No. 453/2010

8. Exposure controls/personal protection (continued)

Hygiene measures: Handle in accordance with good industrial hygiene and safety practices. Do not eat or drink whilst using the product. Wash hands before breaks and at the end of the work day. Wash contaminated clothing before re-use.

Environmental exposure controls: Do not discharge into drains or rivers.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

State and colour Aerosol emitting colourless spray.

Odour Mild

Odour Threshold No data available Flammability Extremely flammable

Flash point <0°C Lower explosion limit 0.8% Upper explosion limit 9.0%

Explosive propertiesNot explosive
Thermal decomposition
No data available

Auto-ignition temperature>230°COxidising propertiesNon-oxidisingSolubility in waterInsoluble

Solubility in other solvents Soluble in most organic solvents.

pH Not applicableMelting point/range No data availableBoiling point/range No data available

Relative density 0.97 g/cm³ @ 20°C (of liquid material)

Vapour pressureNo data availableVapour densityNo data availablePartition coefficient: n-octanol/waterNo data available

Viscosity (kinematic) Non-viscous (liquid material)

Evaporation rate No data available

10. STABILITY AND REACTIVITY

10.1 Reactivity Generally non-reactive.
 10.2 Chemical stability Stable under normal conditions.
 10.3 Possibility of hazardous reactions
 None if stored and used as directed.

10.4 Conditions to avoidNone known.10.5 Incompatible materialsNone known.10.6 Hazardous decomposition productsOxides of carbon.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

Chemical name	Oral (LD50)	Inhalation (LC50)	Dermal (LD50)
Liquefied petroleum gas	Not applicable	>20mg/l (Rat) 4h	Not applicable

Skin corrosion/irritation: Not classed as a skin irritant.

Serious eye damage/eye irritation: Not classed as an eye irritant.

Respiratory or skin sensitisation: Not classed as a respiratory or skin sensitizer.

Page 5 of 7 Issued:09/06/2025; Revision No3 Regulation (EC) No. 453/2010

11.1 Information on toxicological effects (continued)

Repeated dose toxicity: Not expected to be a hazard.

Carcinogenicity: Not carcinogenic.

Mutagenicity: Not mutagenic.

Toxicity for reproduction: Not expected to be a hazard.

Specific target organ toxicity (STOT): No data available.

Further information

The product as a whole may cause irritation of skin, eyes, nose and upper respiratory tract if exposed to high levels of spray mist.

12. ECOLOGICAL INFORMATION

12.1 Toxicity Physical properties indicate that petroleum gases will rapidly volatilise

from the aquatic environment and that acute and chronic effects would

not be observed in practice.

12.2 Persistence and degradability The liquid content (silicone oil) is not readily biodegradable. Liquefied petroleum

gas is expected to be readily biodegradable. Oxidises rapidly by photochemical

reactions in air.

12.3 Bioaccumulative potentialNot expected to bioaccumulate significantly.

12.4 Mobility in soilThe liquid content is insoluble in water and will float on the surface.

12.5 Results of PBT and vPvB assessmentContains no PBT or vPvB substances.

12.6 Other adverse effectsNone expected.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Disposal operations: Dispose of in accordance with local and national regulations.

Contact licensed waste disposal company. Most aerosols can be recycled. Do not pierce or burn or use a cutting torch on the empty aerosol container.

14. TRANSPORT INFORMATION

General Information: The UN number for all aerosols is 1950. Aerosols packed in fibreboard cartons up to 30 kg gross weight, or shrink/stretch wrapped onto trays up to 20 kg gross weight may be transported as Limited Quantities, and should display the following symbol on the pack:

Page 6 of 7 Issued:09/06/2025; Revision No3 Regulation (EC) No. 453/2010

14. Transport information (continued)

The following information relates to all other aerosols not transported as Limited Quantities:

14.1 UN number ADR/RID/ADN; IMDG; ICAO 1950

14.2 UN proper shipping name AEROSOLS

14.3 Transport hazard class(es) ADR/RID/ADN Class 2, 5F

ADR/RID/ADN Class Class 2, Gases

ADR Label No. 2.1

IMDG Class

ICAO Class/Division 2

ICAO Subsidiary risk 2.1



Transport labels

14.4 Packing Group ADR/RID/ADN; IMDG; ICAO Not applicable for aerosols

14.5 Environment hazards Marine Pollutant Not applicable for aerosols.

14.6 Special precautions for user EMS F-D,S-U

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for aerosols.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK Regulatory References

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2001 No.2677) with amendments.

EU Directives

Regulations (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

Statutory Instruments

The Chemicals (Hazard information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

Guidance Notes

Health and Safety Executive Workplace Exposure Limits EH40.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been performed on this product.

Page 7 of 7 Issued:09/06/2025; Revision No3 Regulation (EC) No. 453/2010

16. OTHER INFORMATION

Full text of H-statements referred to under sections 2 and 3

- H220 Extremely flammable gas.H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H280 Contains gas under pressure, may explode if heated.

Abbreviations and acronyms

CAS: Chemical Abstract Service (division of the American Chemical Society). {Section 3}.

STOT: Single Target Organ Toxicity (Section 11).

TWA: Time-weighted average. (Section 8).

STEL: Short-term exposure limit. (Section 8).

PBT: Persistent, Bioaccumulative, Toxic. (Section 12).

vPvB: very Persistent and very Bioaccumulative. (Section 12).

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

[final page]