


HOLLINSEND

HOLLINSEND LED Recessed Emergency Bulkhead, Slave, 50V, White, Prismatic Diffuser

















GENERAL DATA

Depth (mm)

Weight (g)

Light Source	LED
Light Source Replaceable	Yes
Colour/Finish	Chrome
Material	Metal
Diffuser Type	Prismatic
Diffuser Material	Polycarbonate
IP Rating	IP20
Mounting Type	Recessed
Warranty (Years)	5
Life Time Hours	30,000
DIMENSIONS & WEIGHT	
Length (mm)	380
Width (mm)	158

BLE LIGHTING AND POWER LTD

2090

68




ELECTRICAL

LLL CTRIC/ LL			
Input Voltage (V)	50		
Input Frequency (Hz)	50		
Wattage (W)	3		
Classification	Class I		
Operating Temperature (°c)	0 to +40		
Power Factor	0.92		
OPTICAL			
Colour Temperature	5000K		
CRI	80		
Beam Angle (°)	120		
Lumen Output Mains (lm)	250		
EMERGENCY			
Mode Of Operation	CBU Controlled		
STANDARDS & APPROVALS			
Manufactured in Accordance with	BS EN 60598-1, BS EN 60598-2-22		
CE Mark	Yes		
UKCA Mark	Yes		
WEEE Symbol	Yes		
Accredited Members	ISO 9001, LIA, ICEL		
PACKAGING			
Packaging Length (mm)	390		
Packaging Width (mm)	170		
Packaging Depth (mm)	97		

Spacing Tables

BLE LIGHTING AND POWER LTD





SLAVE	OPEN (ANTI-PANIC) AREA (0.5 LUX MINIMUM)				
	+				
Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial	
2.5m	4.2	9.1	3.2	8.0	
3.0m	4.9	10.5	3.4	8.6	
4.0m	6.1	13.4	3.7	9.5	