


HOLLINSEND

HOLLINSEND LED Recessed Emergency Bulkhead, Slave, 110V, Chrome, Opal Diffuser

















GENERAL DATA

LED
Yes
Chrome
Metal
Opal
Polycarbonate
IP20
Recessed
5
30,000

Length (mm)	380
Width (mm)	158
Depth (mm)	68
Weight (g)	1434

BLE LIGHTING AND POWER LTD




ELECTRICAL

Input Voltage (V)	110		
Input Frequency (Hz)	50		
Wattage (W)	3		
Classification	Class I		
Operating Temperature (°c)	0 to +40		
Power Factor	0.92		
OPTICAL			
Colour Temperature	5000K		
CRI	80		
Beam Angle (°)	120		
Lumen Output Mains (lm)	250		
EMERGENCY			
Mode Of Operation	CBU Controlled		
STANDARDS & APPROVALS			
Manufactured in Accordance with	BS EN 60598-1, BS EN 60598-2-22		
CE Mark	Yes		
UKCA Mark	Yes		
WEEE Symbol	Yes		
Accredited Members	ISO 9001, LIA, ICEL		
PACKAGING			
Packaging Length (mm)	390		
Packaging Width (mm)	170		
Packaging Depth (mm)	97		

Spacing Tables

BLE LIGHTING AND POWER LTD





SLAVE	OPEN (AN	OPEN (ANTI-PANIC) AREA (0.5 LUX MINIMUM)				
	+			□		
Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial		
2.5m	4.2	9.1	3.2	8.0		
3.0m	4.9	10.5	3.4	8.6		