


HOLLINSEND

HOLLINSEND LED Recessed Emergency Bulkhead, Slave, 50V, Chrome, Opal Diffuser

















\sim EN	JFRAI	\Box	· A
(70)	JEKAI	1141	Δ

Light Source	LED
Light Source Replaceable	Yes
Colour/Finish	Chrome
Material	Metal
Diffuser Type	Opal
Diffuser Material	Polycarbonate
IP Rating	IP20
Mounting Type	Recessed
Warranty (Years)	5
Life Time Hours	30,000

DIMENSIONS & WEIGHT

Length (mm)	380	
Width (mm)	158	
Depth (mm)	68	
Weight (g)	1434	


ELECTRICAL

BLE LIGHTING AND POWER LTD



Input Voltage (V)	50
Input Frequency (Hz)	50
Wattage (W)	3
Classification	Class I
Operating Temperature (°c)	0 to +40
Power Factor	0.92
OPTICAL	
Colour Temperature	5000K
CRI	80
Beam Angle (°)	120
Lumen Output Mains (lm)	250
EMERGENCY	
Mode Of Operation	CBU Controlled
STANDARDS & APPROVALS	
Manufactured in Accordance with	BS EN 60598-1, BS EN 60598-2-22
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Accredited Members	ISO 9001, LIA, ICEL
PACKAGING	
Packaging Length (mm)	390
Packaging Width (mm)	170
Packaging Depth (mm)	97

Spacing Tables



SLAVE	OPEN (ANTI-PANIC) AREA (0.5 LUX MINIMUM)			
	*			□ ↔□
Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
2.5m	4.2	9.1	3.2	8.0
3.0m	4.9	10.5	3.4	8.6
4.0m	6.1	13.4	3.7	9.5

BLE LIGHTING AND POWER LTD