


## **HOLLINSEND**

# HOLLINSEND LED Recessed Emergency Bulkhead, Slave, 24V, White, Opal Diffuser

















### **GENERAL DATA**

Light Source	LED
Light Source Replaceable	Yes
Colour/Finish	White
Material	Metal
Diffuser Type	Opal
Diffuser Material	Polycarbonate
IP Rating	IP20
Mounting Type	Recessed
Warranty (Years)	5
Life Time Hours	30,000
·	

### **DIMENSIONS & WEIGHT**

Length (mm)	380
Width (mm)	158
Depth (mm)	68
Weight (g)	1434


#### **ELECTRICAL**

#### **BLE LIGHTING AND POWER LTD**



Input Voltage (V)	24		
Input Frequency (Hz)	50		
Wattage (W)	3		
Classification	Class I		
Operating Temperature (°c)	0 to +40		
Power Factor	0.92		
OPTICAL			
Colour Temperature	5000K		
CRI	80		
Beam Angle (°)	120		
Lumen Output Mains (lm)	250		
EMERGENCY			
Mode Of Operation	CBU Controlled		
STANDARDS & APPROVALS			
Manufactured in Accordance with	BS EN 60598-1, BS EN 60598-2-22		
CE Mark	Yes		
UKCA Mark	Yes		
WEEE Symbol	Yes		
Accredited Members	ISO 9001, LIA, ICEL		
PACKAGING			
PACKAGING Packaging Length (mm)	390		
	390 1 <i>7</i> 0		

### **Spacing Tables**



SLAVE	OPEN (ANTI-PANIC) AREA (0.5 LUX MINIMUM)			
	<b>+</b>		<b>+</b>	<b>□</b> ↔□
Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
2.5m	4.2	9.1	3.2	8.0
3.0m	4.9	10.5	3.4	8.6
4.0m	6.1	13.4	3.7	9.5

#### **BLE LIGHTING AND POWER LTD**