


## **MEERSBROOK**

# MEERSBROOK LED 5 in 1 Exit Sign, 3.2V LiFePO4 Battery, Self Test























## **GENERAL DATA**

Light Source	LED
Light Source Replaceable	No
Colour/Finish	White
Material	Polycarbonate
IP Rating	IP20
IK Rating	IKO8
Mounting Type	Ceiling / Recessed / Flag / Hanging / Wall Mount
Warranty (Years)	5
Life Time Hours	50,000
DIMENSIONS & WEIGHT	

Width (mm)	344
Depth (mm)	42
Height (mm)	237
Weight (g)	1556

#### **BLE LIGHTING AND POWER LTD**



## **ELECTRICAL**

ELECTRICAL	
Input Voltage (V)	220-240
Input Frequency (Hz)	50
Wattage (W)	2.8
Classification	Class I
Operating Temperature (°c)	0 to +40
Power Factor	0.56
OPTICAL	
Colour Temperature	6500K
CRI	70
Beam Angle (°)	96
Lumen Output Mains (lm)	37
Viewing Distance (M)	29
EMERGENCY	
Battery Type	LiFePO4 18650 3.2V
Battery Capacity	1.5Ah
Battery Warranty (Years)	5
Recharge Time (hrs)	24
Battery Replaceable	Yes
Mode Of Operation	Maintained / Non-maintained
Test Procedure	Self Test
Emergency Duration (Hrs)	3
Lumen Output Emergency (lm)	27
STANDARDS & APPROVALS	
Manufactured in Accordance with	BS EN 60598-1, BS EN 60598-2-22
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Accredited Members	ISO 9001, LIA, ICEL
PACKAGING	
Packaging Length (mm)	385

## **BLE LIGHTING AND POWER LTD**

# DATA SHEET EL-131950



Packaging Width (mm)	365
Packaging Depth (mm)	75

## **BLE LIGHTING AND POWER LTD**