

PRODUCT

FV-PRO 9544A3B-PA - 4MP Fixed 2.8mm AI Turret IP Camera with active deterrent, warning message and 2 way audio



Features

Blue and red light warning (flashing alternately)

Support user-defined warning voice import

1CH audio input; 1CH built-in speaker; 1CH built-in MIC

Intelligent analytics:

abnormal video signal detection (scene change, video cast & video blur detection),

line crossing detection (human/vehicle classification),

region intrusion/entrance/exiting detection (human/vehicle classification)

H.265+/H265/H.264+/H264/MJPEG coding

Max.resolution:2592 × 1520

ICR auto switch, true day / night

30 ~ 50m IR night view distance

3D DNR, true WDR, HLC, BLC, Defog and ROI coding

Built-in micro SD card slot, up to 256GB

DC12V/PoE power supply

IP66 ingress protection

Support three streams

Support remote monitoring by smart phones & tablet

PCs with iOS and Android OS)

DETAILS

ADDITIONAL INFORMATION

Alarm Inputs / Relay Outputs

1CH alarm input; 1CH alarm output

Audio Inputs	1CH audio input; 1CH built-in speaker; 1CH built-in MIC
BLC	Yes
BLC/SSDR (WDR)	120dB
Compression Method	Smart H.265 / H.265+ / H.265 / Smart H.264 / H.264+ / H.264 / MJPEG
DNR	3D DNR
Dimensions	Ø111.5 × 99.6
Image Sensor (CCD)	1 / 3" CMOS
Lens	2.8mm FIXED
Minimum Illumination - Colour	0.0028 lux
Minimum Illumination - Mono	0 lux with IR
Operating Temperature	- 30 °C ~ 60 °C (-22°F~140°F)
POE	Yes
Power Consumption	< 11W
Power Source	DC12V/PoE
Remote Interface	Web Client/NVR/NVMS2.0/Mobile APP
Resolution (Best)	4MP (2592 × 1520)
Shutter	1 s ~ 1 / 100000 s
Storage Media & Capacity	Built-in micro SD card slot; up to 256GB
Weight(Cameras)	Approx. 0.64KG
Within Range of IR LEDs	30 ~ 50 m