

FV-PRO 9453E2A-AZ - 5 Megapixel Motorised Zoom
2.8-12mm Auto Focus H265 / H264 Real Time External IP
Bullet Style Camera



Features

5MP (2592 × 1944) H.265 full real time
coding

Max.resolution: 2592 × 1944

ICR auto switch, true day / night

50 ~ 70m IR night view distance

Motorized zoom lens

3D DNR, true WDR, HLC, BLC, Smart IR and
ROI coding

One CVBS output and one on-board CVBS
output

1CH audio input and 1CH audio output

Hardware reset

Built-in micro SD card slot, up to 128GB

1CH alarm input; 1CH alarm output

RS485

DC12V/PoE power supply

IP67 protection grade

Support smart phone, iPad, remote
monitoring

Support three streams

P2P function optional

Support face detection

Smart analytics (optional): object removal
detection, abnormal video signal detection,
line crossing detection, region intrusion
detection, people intrusion detection, people
counting detection and crowd density
detection

DETAILS

5MP IP Auto Focus IR Bullet camera with a 2.8-12mm Varifocal Lens

ADDITIONAL INFORMATION

AES	Yes
AGC	Auto
Aperture Correction	H aperture V aperture
BLC	Yes
BLC/SSDR (WDR)	True WDR
Connection Cable	DC + POE / Video / Audio (RJ45)
DNR	2D + 3D
Dimensions	279.5mm × 100.3mm × 88.9mm
Dual Streaming	3 Streams
Effective Pixel	2592(H) x 1944(V)
Enhancement	Yes
Gamma Correction	0.45
Image Sensor (CCD)	1/3" CMOS 5MP
Lens	2.8~12mm Megapixel Auto Focus Day / Night ICR Lens
Minimum Illumination - Colour	0.036 lux @F2.0, AGC ON; 0.013 lux @ F1.2, AGC ON; 0 lux with IR
Minimum Illumination - Mono	0 Lux with IR LED's on
Model	IPC9453E2A-AZ
POE	Yes
Power Consumption	<7W
Power Source	12V DC Regulated or POE
Privacy	Yes
RS485 Interface	Yes
S/N Ratio	52db +
Scanning System	Yes
Shutter	1/25s ~ 1/100000s
Storage Media & Capacity	Network remote storage; micro SD card storage
Sync System	2:1 Internal
Sync. Type	Internal
Video Output Signal	1.0vp-p, 75 ohm composite
Video output	IP and BNC

Within Range of IR LEDs	50-70m
Zoom	Yes - Auto