



SAFETY DATA SHEET

Page 1 of 8
Issued: 09/06/2025; Revision No3
Regulation (EU) No. 453/2010

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1 Product Identifier

Material name : Loose Juice LJ2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Lubricant for pneumatic tools.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Gas Safe Europe Ltd
Chowley One
Chowley Oak Lane
Tattenhall, Chester
United Kingdom
CH3 9GA
Tel. : 00 44 (0) 1352 860600

Email (for SDSs) : enquiries@gassafeeurope.com

1.4 Emergency tel. no.: 00 44 (0) 1352 860600 office hours

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

According to 1272/2008/EC: Classification, Labelling and Packaging of Substances and Mixtures (CLP) Regulation:

Extremely Flammable Aerosol Category 1
Skin Irritant 2
STOT SE Category 3
Aquatic Chronic 2

2.2 Label elements

Labelling according to EC Directives: 1272/2008/EC:

Signal word: Danger



Pictogram(s):

Contains: Distillates (Petroleum) Hydrotreated Light

| | | |
|---------------|------|--|
| H-Statements: | H222 | Extremely flammable aerosol. |
| | H229 | Pressurised container: May burst if heated. |
| | H315 | Causes skin irritation. |
| | H336 | May cause drowsiness or dizziness. |
| | H411 | Toxic to aquatic life with long lasting effects. |

SAFETY DATA SHEET

Page 2 of 8
Issued: 09/06/2025; Revision No3
Regulation (EU) No. 453/2010

2.2 Label elements (continued)

| | | |
|-----------------------------|-------------|---|
| P-Statements: | P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| | P211 | Do not spray on an open flame or other ignition source. |
| | P251 | Do not pierce or burn, even after use. |
| | P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 50°C. |
| | P261 | Avoid breathing vapour/spray. |
| | P280 | Wear protective gloves. |
| | P271 | Use only outdoors or in a well-ventilated area. |
| | P302+P352 | IF ON SKIN: Wash with soap and water. |
| | P304 + P340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| | P273 | Avoid release to the environment. |
| Supplementary P-Statements: | P332+P313 | If skin irritation occurs: Get medical advice/attention. |
| | P362 | Take off contaminated clothing and wash before re-use. |
| | P501 | Dispose of in accordance with local/national regulations. |

2.3 Other hazards In use, may form flammable / explosive vapour-air mixture.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures:

Hazardous components

| Chemical Name | CAS No./ EC No./ Reg. No | Classification (1272/2008/EC) | Content |
|---|---|---|---------|
| DISTILLATES (PETROLEUM) HYDROTREATED LIGHT 0 | 64742-47-8 265-149-8 01-2119484819-18 | Skin Irrit. 2 H315, Asp. Tox. 1 H304, STOT SE 3 H336, Aquatic Chronic 2 H411 | 50-70% |
| LIQUEFIED PETROLEUM GAS (contains <0.1% 1,3-butadiene) | 68476-85-7 270-704-2 - | Flam.Gas 1; H220 Gas under pressure; H280 | 10-30% |

See Section 16 for the full text of the H-statements noted above.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice: Remove casualty from exposure ensuring one's own safety whilst doing so. Take off any contaminated clothing and shoes/boots immediately. Never give anything by mouth to an unconscious person.

Skin contact: Wash with soap and water. Seek medical advice if irritation develops.

Eye contact: Rinse with water for 10 minutes and seek medical advice if irritation persists.

Ingestion: Rinse mouth with water and give water to drink. Do not induce vomiting. Seek medical advice.

Inhalation: Remove to fresh air. Seek medical advice.

4. First Aid Measures (continued)

4.2 Most important symptoms and effects, both acute and delayed: May cause irritation to skin and eyes with prolonged contact.

4.3 Indication of any immediate medical attention and special treatment needed: See skin and eye contact information above.

5. FIRE-FIGHTING MEASURES**5.1 Extinguishing media**

Suitable extinguishing media: Carbon dioxide; dry chemical powder; alcohol or polymer foam.

Unsuitable extinguishing media: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting: Irritating/toxic fumes may be released at elevated temperatures.

5.3 Advice for fire-fighters:

Special protective equipment: Wear self-contained breathing apparatus. Use personal protective equipment.

Further information: Standard procedure for chemical fires. Use water spray to cool containers.
Do not allow fire run-off to enter drains.

6. ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures**

Evacuate personnel to safe areas. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Use personal protective equipment to deal with spillage.

6.2 Environmental precautions

Contain the spillage using sufficient appropriate absorbent material. Do not discharge into drains or rivers, but if contamination to waterways has occurred, inform local authorities.

6.3 Methods and materials for containment and cleaning up

Wipe up liquid spillage with absorbent material such as sand, earth, or vermiculite, and place in a labelled container for disposal in accordance with local/national regulations.

6.4 References to other sections

See sections 8 and 13 for personal protection and disposal information.

7. HANDLING AND STORAGE**7.1 Precautions for safe handling**

Do not breathe spray mist. Avoid contact with skin and eyes. Handle with care.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, well ventilated area, below 50°C. Protect from frost, heat and sunlight. Keep away from food, drink and animal feed.

7.3 Specific end use(s): No information available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**8.1 Control parameters**

| Chemical name | 8hr TWA | 15min STEL | Reference |
|--|---------------------------------|----------------------------------|-----------|
| Distillates (Petroleum) Hydrotreated Light | 200 mg/m ³ | - | Supplier |
| Liquefied petroleum gas | 1750 mg/m ³ /1000ppm | 2810 mg/m ³ /1250 ppm | EH40/2005 |

8.2 Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Personal protective equipment

Respiratory protection: Unlikely to be necessary in normal circumstances; if vapour levels are high, wear a respirator conforming to EN 140 with type A filter or better.

Hand protection: Wear chemically resistant gloves such as butyl rubber approved to standard EN 374; material thickness 0.5mm; break through time \geq 480 min. Gloves must be replaced after 8 hours of wear. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Check with glove manufacturer for specific advice.

Eye protection: Chemical splash goggles if eye contact is reasonably probable. The selected goggles or glasses must satisfy the European standard EN 166.

Skin and body protection: Depending on the conditions of use, protective gloves, apron, boots, head and face protection should be worn. The selected protective clothing has to satisfy the standard EN 13034, which describes clothing offering limited 8 hour protection against splashes. Use PPE that is chemically resistant to the product and prevents skin contact.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practices. Do not eat or drink whilst using the product. Wash hands before breaks and at the end of the work day. Wash contaminated clothing before re-use.

Environmental exposure controls: Do not discharge into drains or rivers.

9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties**

| | |
|------------------------------|--|
| State and colour | Aerosol emitting light brown coloured spray. |
| Odour | Paraffinic |
| Odour Threshold | No data available |
| Flammability | Extremely flammable |
| Flash point | <0°C |
| Lower explosion limit | 0.8% |
| Upper explosion limit | 9.0% |
| Explosive properties | Not explosive |
| Thermal decomposition | No data available |
| Auto-ignition temperature | >230°C |
| Oxidising properties | Non-oxidising |
| Solubility in water | Insoluble |
| Solubility in other solvents | Soluble in most organic solvents. |
| pH | Not applicable |
| Melting point/range | No data available |
| Boiling point/range | No data available |
| Relative density | No data available |

SAFETY DATA SHEET

Page 5 of 8
Issued: 09/06/2025; Revision No3
Regulation (EU) No. 453/2010

9.1 Information on basic physical and chemical properties (continued)

| | |
|--|-------------------|
| Vapour pressure | No data available |
| Vapour density | No data available |
| Partition coefficient: n-octanol/water | No data available |
| Viscosity (kinematic) | No data available |
| Evaporation rate | No data available |

9.2 Other information

| | |
|-------------|-----|
| VOC Content | 88% |
|-------------|-----|

10. STABILITY AND REACTIVITY

| | |
|---|--------------------------------------|
| 10.1 Reactivity | Generally non-reactive. |
| 10.2 Chemical stability | Stable under normal conditions. |
| 10.3 Possibility of hazardous reactions | None if stored and used as directed. |
| 10.4 Conditions to avoid | None known. |
| 10.5 Incompatible materials | None known. |
| 10.6 Hazardous decomposition products | Oxides of carbon. |

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

| Chemical name | Oral (LD50) | Inhalation (LC50) | Dermal (LD50) |
|--|-------------------|-------------------|----------------------|
| Distillates (Petroleum) Hydrotreated Light | >5000 mg/kg (Rat) | >5 mg/l (Rat) 4h | >2000 mg/kg (Rabbit) |
| Liquefied petroleum gas | Not applicable | >20mg/l (Rat) 4h | Not applicable |

| | |
|---|--|
| Skin corrosion/irritation: | Irritating to skin. |
| Serious eye damage/eye irritation: | Not classed as an eye irritant. |
| Respiratory or skin sensitisation: | Not classed as a respiratory or skin sensitizer. |
| Repeated dose toxicity: | Not expected to be a hazard. |
| Carcinogenicity: | Not carcinogenic. |
| Mutagenicity: | Not mutagenic. |
| Toxicity for reproduction: | Not expected to be a hazard. |
| Specific target organ toxicity (STOT): Single exposure | High levels of vapour may cause central nervous depression; headache, dizziness, nausea. |
| Specific target organ toxicity (STOT): Repeated exposure | Not expected to be a hazard. |

Further information

The product as a whole may cause irritation of skin and upper respiratory tract if exposed to high levels of spray mist.

12. ECOLOGICAL INFORMATION**12.1 Toxicity**

| Chemical name | Species | Test | Value |
|--|---------|----------|-----------|
| Distillates (Petroleum) Hydrotreated Light | Daphnia | EC50 48h | 1-10 mg/l |
| | Fish | LL50 96h | 1-10 mg/l |
| | Algae | EC50 72h | 1-10 mg/l |

Physical properties indicate that petroleum gases will rapidly volatilise from the aquatic environment and that acute and chronic effects would not be observed in practice.

12.2 Persistence and degradability

Liquefied petroleum gas is expected to be readily biodegradable. Oxidises rapidly by photochemical reactions in air. The solvent content is expected to be inherently biodegradable.

12.3 Bioaccumulative potential

Contains constituents expected to bioaccumulate.

12.4 Mobility in soil

The liquid content is insoluble in water and will float on the surface.

12.5 Results of PBT and vPvB assessment

Contains no PBT or vPvB substances.

12.6 Other adverse effects

None expected.

13. DISPOSAL CONSIDERATIONS**13.1 Waste treatment methods**

Disposal operations: Dispose of in accordance with local and national regulations.
Contact licensed waste disposal company. Most aerosols can be recycled.
Do not pierce or burn or use a cutting torch on the empty aerosol container.

14. TRANSPORT INFORMATION

General Information: The UN number for all aerosols is 1950. Aerosols packed in fibreboard cartons up to 30 kg gross weight, or shrink/stretch wrapped onto trays up to 20 kg gross weight may be transported as Limited Quantities, and should display the following symbol on the pack:



The following information relates to all other aerosols not transported as Limited Quantities:

| | | |
|--|-------------------------|----------------|
| 14.1 UN number | ADR/RID/ADN; IMDG; ICAO | 1950 |
| 14.2 UN proper shipping name | AEROSOLS | |
| 14.3 Transport hazard class(es) | ADR/RID/ADN Class | 2, 5F |
| | ADR/RID/ADN Class | Class 2, Gases |
| | ADR Label No. | 2.1 |
| | IMDG Class | 2 |

SAFETY DATA SHEET

Page 7 of 8
Issued 09/06/2025; Revision No.3
Regulation (EU) No. 453/2010

14. Transport Information (continued)

ICAO Class/Division 2
ICAO Subsidiary risk 2.1



Transport labels

14.4 Packing Group ADR/RID/ADN; IMDG; ICAO Not applicable for aerosols

14.5 Environment hazards Marine Pollutant Not applicable for aerosols.

14.6 Special precautions for user EMS F-D, S-U

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable for aerosols.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK Regulatory References

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2001 No.2677) with amendments.

EU Directives

Regulations (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

Statutory Instruments

The Chemicals (Hazard information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

Guidance Notes

Health and Safety Executive Workplace Exposure Limits EH40.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been performed on this product.

16. OTHER INFORMATION

This safety data sheet is prepared in accordance with Commission Regulation (EU) No.453/2010.

Full text of H-statements referred to under sections 2 and 3

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms

CAS: Chemical Abstract Service (division of the American Chemical Society). {Section 3}.

STOT: Single Target Organ Toxicity (Section 2; 11).

SE: Single exposure (Section 2)

TWA: Time-weighted average. (Section 8).

STEL: Short-term exposure limit. (Section 8).

PBT: Persistent, Bioaccumulative, Toxic. (Section 12).

vPvB: very Persistent and very Bioaccumulative. (Section 12).

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

[final page]