

SFX/59-PVC-BLK

RG59 Coaxial CCA Black PVC



Cable Construction

| | |
|---------------------------|------------------------|
| Inner Conductor | Copper Clad Steel |
| Conductor Diameter (mm) | 0.58 ±0.008 |
| Insulation | Solid PE |
| Insulation Thickness (mm) | 1.60 ±0.01 |
| Insulation Diameter (mm) | 3.70 ±0.10 |
| Insulation Colour | Clear |
| Braid | Copper Clad Aluminium |
| Braid Construction | 0.12 ±0.008 x 16 x 7 |
| Braid Coverage | 85% |
| Jacket | PVC |
| Jacket Thickness (mm) | 0.85 ±0.10 |
| Overall Diameter (mm) | 6.10 ±0.10 |
| Jacket Colour | Black RAL 9005 |
| Sheath Printing | RG59 PVC RoHS (PO) (m) |
| Reaction to Fire | Eca |

Electrical Characteristics

| | |
|--------------------------------------|----------|
| Inner Conductor DC resistance @ 20°C | <216Ω/km |
| Outer Conductor DC resistance @ 20°C | <48Ω/km |
| Rated Temperature | 80°C |
| Impedance | 75Ω ±3Ω |
| Capacitance | >67nF/km |
| Nominal Velocity Ratio | 66.70% |