



MODEL NUMBER

SD-8EL

SPECIFICATIONS

FREQUENCY

868 MHz / 433 MHz

POWER

Alkaline AA x 3

BATTERY LIFE

4.5* years

* Note: Battery life is calculated at an average of 20 activations per day.

OPERATING TEMPERATURE

-10°C to 45°C (14°F to 113°F)

OPERATING HUMIDITY

Up to 85% non-condensing

DIMENSIONS

Diameter ø 105mm x 42mm

CERTIFICATIONS

CE, RCM, MTC, SUBTEL, NOM, IFT, SIRIM, IMDA, SIGET, ARCOTEL, URSEC, SUTEL



Smoke Detector

- Alarm Volume: 85 dB at 3 meter
- Built-in siren for audio alert
- Alarm silence function: 10 minutes per activation
- Diagnostic function: a test button for self-test including optical sensor diagnosis
- Excellent stability with high sensitivity
- Low battery detection
- Randomized supervision signals for trouble-free system integrity checking
- Digital signal processing
- Detection method: Reflective photoelectric sensor

DESCRIPTION

The Smoke Detector SD-8EL is low profile and small in size. It utilizes the latest Optical Chamber technology to detect potentially harmful smoke particles. It is micro-process controlled with 100% reliability.

SD-8EL provides the best safety and quality against potential fire hazard.

SERVICE PACKAGES

- Commercial
- Commercial Plus
- Interactive
- Interactive + Automation
- Interactive Gold