

SFX/OSP6-LSZH-GRY

OSP6 6pr 24AWG Overall Foil Screen 600V Grey LSZH (9506)



<b>Cable Construction</b>	6 Pairs
Conductor	Tinned Copper
Conductor Diameter (mm)	0.19 ±0.008 x 8
Stranded Diameter (mm)	0.60
<b>Insulation</b>	LSZH
Insulation Thickness (mm)	0.28
Insulation Diameter (mm)	1.25 ±0.10
Insulation Colours	Red,Black;White,Black;Green,Black;Blue,Black;Yellow,Black;Brown,Black
<b>Al-PET Shield</b>	≥115%
<b>Drain Wire</b>	
Conductor	Tinned Copper
Conductor Diameter (mm)	0.19 ±0.008 x 8
<b>Jacket</b>	LSZH
Jacket Thickness (mm)	0.70
Overall Diameter (mm)	7.20 ±0.20
Jacket Colour	Grey RAL 7042
Sheath Printing	OSP6 6x2x24AWG Overall Foil Screened LSZH RoHS2 (PO) (m)
Reaction to Fire	Eca
<b>Electrical Characteristics</b>	
Max Conductor DC resistance @ 20°C	<79.00Ω/km
Rated Temperature	70°C
Rated Voltage	600V
Insulation Resistance @20°C	>200MΩ/km